



# 555 Series


## Covered Wall Unit

**Application:** This covered wall unit is designed to provide maximum lumen output in areas such as hallways, bathrooms, kitchens, stairways, and hospitals. An assortment of options in either single or double lamp allows this utility wall and surface mounted unit to satisfy a variety of lighting needs.


**Construction:** Housing is designed from heavy gauge die formed steel and finished in either baked white enamel or polyester powder coating. Socket plate is riveted to housing adding to the structural support of the fixture. Lens is extruded white acrylic. End plates are attached by acorn nuts and secure the lens to the fixture.

**Electrical:** All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request. Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standards.

**Mounting:** Unit is equipped with holes and 7/8" knockouts in housing for surface mounting. Fixture may be mounted individually or with optional joiner bands may be used in a continuous run.



Fixture Length			
T12	T12HO	T8	Length
F15T12	---	---	18"
F20T12	---	F17T8	24"
F30T12	---	F25T8	36"
F40T12	F48T12HO	F32T8	48"



Maximum Weight = 12 lbs. / 48"

### Ordering Information

Specifications Subject To Change Without Notice

Model	# Lamps	Lamp Type	Ballast	Voltage	Options
<b>555-</b>	<b>2</b>	<b>32</b>	<b>E</b>		
555	1 = One 2 = Two	<b>T8 Lamps</b> 17 = F17T8 25 = F25T8 32 = F32T8 <b>T12 Lamps</b> 15 = F15T12 20 = F20T12 30 = F30T12 40 = F40T12	M = Magnetic E = Electronic .88 BF E-LW = Electronic .77 BF E-O = Electronic 1.18 BF	Blank = 120V 277 = 277 V MV = Multi Volt	O = Grounded Outlet TOG = Toggle Switch ROC = Rocker Switch PULL = Pull Switch EMB = Emergency Ballast NL = Night Light 3WAY = 3 Way System

