

# DBEL Decorative Outdoor LED Emergency Unit

<b>Project:</b>	
<b>Type:</b>	
<b>Catalog #:</b>	



**STANDARD**



**OPTIONAL**



**ILLUMINATION**

- Long-life, efficient ultra-bright white LED.
- 5 watt LED per unit.
- Mirror-bright reflector and prismatic polycarbonate refractor.

**ELECTRICAL**

- Dual 120/277 voltage.
- Charge rate/power“ON”LED indicator light and push to test switch for mandated code compliance testing.
- 4.8V long-life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.
- Self-diagnostic test feature continually diagnoses units performance and tests system to ensure reliable operation and to meet electrical and life safety codes.

**MOUNTING**

- Surface mount via easy connect back plate that fits most standard size junction boxes.
- Universal K/O pattern on back plate for wall mount.

**HOUSING**

- Decorative, low-profile, architectural design.
- Die-cast aluminum housing.
- Durable powder-coated finishes in white, black and dark bronze.
- Sealed and gasketed.


**OPTIONS**

- CW: Cold-weather unit for use in freezer applications. (in temperatures as low as (-20°C – 40°C)

**WARRANTY/LISTING**

- Five year warranty on all electronics and housing. Battery pro-rated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL listed for wet locations. (0°C – 50°C)

**DIMENSIONS**



**ORDERING INFORMATION**

Sample Part Number: DBEL-BR-SDT

Model	Housing Color	Options	
DBEL	W White B Black BR Dark Bronze	SDT Self-diagnostics	CW Cold Weather

Specifications Subject To Change Without Notice