KB LIGHTING

LUNAR LED

Outdoor Weatherproof LED

Project:	
Type:	
Catalog #:	

Available in LED

Powder Coated Cast Aluminum

Wall or Ceiling Mount

Enclosed & Gasketed

ETL Listed for Wet Locations (IP65)

Standard Pack QTY: 6

LUNAR

FL372



FL371



LED

IP65

ETL

RoHS compliant

ASK ABOUT ENERGY STAR

EXAMPLE # FL371-LE1200W-BWM

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FL371 **FL372**	**EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40˚C TO +40˚C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR**	**B**-Black **W**-White	**POLYCARBONATE** **W**-White	**M**-Motion Sensor

LE1200 - 14W Power Input, CRI 80 (TYP), >80 Lumens Per Watt** — **W**-1350lm 3000K, **C**-1400lm 4000K

LE1800 - 23W Power Input, CRI 80 (TYP), >80 Lumens Per Watt** — **W**-1850lm 3000K, **C**-1900lm 4000K

*DATA PER LM79/LM80/TM21 & IES FILES AVAILABLE UPON REQUEST **ESTIMATED FROM LED SOURCE

Specifications Subject To Change Without Notice