

Project:	
Type:	
Catalog #:	

Specification Features

2x2

Length 23.80"
 Width 23.80"
 Height 2.70"
 Weight 6.7 lbs

2x4

Length 47.80"
 Width 23.80"
 Height 2.70"
 Weight 12.5 lbs

Housing

White cold rolled steel

Lens

Frosted polycarbonate

Finish

Post painted matte white with minimum 90% reflectivity

Mounting

Installs in standard NEMA 15/16" Type G or NFG T-Grid systems

Light Source 2x2

19" A.L.P. Module 126 LEDs
 25w Universal (120-277Vac) A.L.P. Driver
 Class II, 0-10 v dimming

Light Source 2x4

44" A.L.P. Module 200 LEDs
 36w Universal (120-277Vac) A.L.P. Driver
 Class II, 0-10 v dimming



For the most current listing of DLC Qualified Products, please visit the DLC website www.designlights.org

Retrofit LED Troffer RRT Series 2x2 and 2x4



General Description

The RRT series has been designed as a sleek recessed retrofit kit. It is designed to update an existing fluorescent light fixture. The RRT series is designed to have even illumination from end to end.

Features and Benefits

- Low overall height allows for installation in tight applications.
- Glare-free polycarbonate lens is removable for ease of cleaning.
- ARRT Series is available in both 2x2 and 2x4 configurations, as well as 2 CCT options (3500K and 4000K).

Regulatory Compliance

- DLC 4.1 QPL as premium
- UL for damp locations
- Type IC applications
- cETLus
- LED light engine, UR and UL components
- RoHS compliant
- Five year warranty

Application

Suitable for interior applications including; office, hotel, education, healthcare, and retail environments.

Specifications Subject To Change Without Notice

K-B Lighting Mfg. Co., Inc

2515 Metropolitan Drive Treose PA 19053

P: (215)953-6663 F: (215)953-6710 E: bkessel@kblighting.com

www.kblighting.com