

AP Series

Project:	
Type:	
Catalog #:	

STANDARD





This covered chrome channel can be mounted both vertically and horizontally and comes in a variety of sizes for a wide range of uses. It is Ideal for use in bathrooms, kitchens, powder rooms, under cabinets, or any area where high quality and low cost lighting is preferred.

Construction:

 Housing is designed from heavy gauge die formed steel and plated in a high polished chrome for high grade appearance. Off and on switch is standard in end plate. Snap in grounded convenience outlet is available upon request. End plates are secured to fixture by acorn nuts. Lens is extruded white acrylic.

All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request. Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standard. All units are UL certified damp location

M 59006648

Mounting


Holes and knockouts are provided in units for surface or wall mounting either vertically or horizontally.


1 = 1 Lamp

Chrome Covered Bathroom Wall Unit



WARRANTY & LISTINGS







DIMENSIONS

T12	Т8	Length
F15T12		18 1/2"
F20T12	F17T8	24 1/2"
F30T12	F25T8	36 1/2"
F40T12	F32T8	48 1/2"

Ordering Guide

1P

1P
Series # of Lamps Lamp Size

T8

T12

17 = F17T8

25 =F25T8

32 = F32T8"

14= F14T12

15= F15T12

20 = F20T12 **30** = F30T12 **40** = F40T12 Ballast Type

MV = Multivolt 120 = 120 Volt 277 = 277 Volt

<u>T5</u> 14 = F14T5

21 = F21T5

28 = F28T5

24 = F24T5

39 = F39T5"

54 = F54T5

T5HO

SET LED N = Wired 1 end hot for LED tubes
SET LED N/S = Wired 2 ends hot for LED tube

SET LED N/S = Wired 2 ends hot for LED tubes LEDIF = ballast driven LED Tubes

Max weight = 10lbs / 48"

Options

O = Grounded Outlet **TOG** = Toggle Switch **ROC** = Rocker Switch

PULL = Pull Switch

EMB = Emergency Ballast