

## Wrap Around Surface Mount Units

Project:	
Type:	
Catalog #:	



### STANDARD



This surface mounted wrap around unit is designed for use in most commercial, residential, and institutional type applications. The unit provides maximum light output with minimum clearance.

### Construction:

- Housing is designed from heavy gauge die formed steel and is finished in baked white enamel or polyester powder coating for maximum durability and reflectivity. Clear acrylic prismatic wrap around diffuser hinges from either side and snaps on and off for easy maintenance.

### Electrical

All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request. Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standard. All units are UL certified damp location

### Mounting


Unit is equipped with knockouts and holes for pendant or surface mounting. This Fixture can be mounted individually or continuous run.

### WARRANTY & LISTINGS

- 5-year warranty of all electronics and housing.
- UL Certified for damp location



### DIMENSIONS



### Fixture Length

T12	T8	T5	Length
F20T12	F17T8	F14T5	24"
F40T12	F32T8	F28T5	48"
F96T12	F96T8	---	96"

### For Tandem Units:

Multiply lamp length above by lamp quantity

Fixture	Bulb Spacing
2 Tube	5 3/8"
4 Tube	2 1/4" - 5 3/8" - 2 1/4"
2 Tube in 4 Tube Housing	7"

max weight= 16lbs/48 32lbs/96"

### Ordering Guide

201 LED

#### Series

&\$1 LED

#### Size

2 = 2FT  
4 = 4FT  
6 = 6FT  
8 = 8FT

#### Lumens

**2FT**  
3166 (17W)  
4350 (24W)  
5470 (31W)  
6452 (39W)

#### Color

3K  
35K  
4K  
5K

#### Options

EMBA = Emergency driver  
REFS = Silver Reflector  
OCC-E = External Occupancy Sensor  
FR = Frosted Lens over LED Board

\*\$!%\$j ^ck 'j c'lu[ Y'X]a a ]b[ 'gHUbXUF' dYf' z] li fY'

\*<][ \ Yf'UbX'W gtrca ''i a Yb'dUW\_U[ Yg' Uj Uj'UV'Yi dcb'fYei Ygi

\*Call Factory for lumen options of 3FT and 6FT models

**4FT**  
3220 (17W)  
4480 (24W)  
5705 (30W)  
6910 (37W)  
8640 (48W)  
11797 (70W)

**8FT**  
3220 (17W)  
4480 (24W)  
5705 (30W)  
6910 (37W)  
8640 (48W)  
11797 (70W)  
13820 (74W)  
17280 (96W)  
23594 (140W)