

## Small Wrap Around Surface Mount Units

<b>Project:</b>	
<b>Type:</b>	
<b>Catalog #:</b>	

## STANDARD



V@A"·!-aaÁ[~]c'aÁ!aA[~!~!Á)aaÁ·a)^(aÁ!Á  
 ·^aaÁ·c@{({&aaÁ·aa)aaÁaaÁ·aaq)aaÁ)^(a  
 aa)aaÁ·E@A)aa[~aa^·Aaa{A@a)q'c)aa  
 {aa}Aaa&A

**Construction:**

- Housing is designed from heavy gauge die formed steel and is finished in baked white enamel or polyester powder coating for maximum durability and reflectivity. Clear acrylic prismatic wrap around diffuser hinges from either side and snaps on and off for easy maintenance.

## Electrical

All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request. Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standard. All units are UL certified damp location M 59006648

## Mounting

Wj ā̃<sup>h</sup> Ā<sup>~</sup> ā ] ^āĀ ācā } [ & [ ~ ° ā āā | • Ą : Ą  
] ^) āā oĴ | Ą<sup>~</sup> -āĀ [ ~ ] cā \* Ē / @ Ąc | ^āā āā  
{ [ ~ ] cāā āāā āā^ Ą | & } cā [ ~ • Ą } Ē




## WARRANTY & LISTINGS

- 5-year warranty of all electronics and housing.
- UL Certified for damp location M 59006648




## DIMENSIONS



Coefficients Utilization Zonal Cavity Method												
RF	20											
RC	80%				70%				50%			
RW	70	50	30	10	70	50	30	10	70	50	30	10
0	80	80	80	80	78	78	78	78	73	73	73	73
1	74	72	68	66	72	69	67	64	65	63	63	62
2	68	63	59	55	66	61	58	54	58	55	53	53
3	63	56	51	48	61	55	51	47	53	49	46	46
4	58	51	45	41	56	49	44	41	47	43	40	40
5	53	45	40	35	52	44	39	35	42	38	34	34
6	49	41	35	31	48	40	35	31	38	34	30	30
7	46	37	31	27	44	36	31	27	35	30	27	27
8	42	33	28	24	41	33	27	24	31	27	23	23
9	39	30	24	21	38	29	24	21	28	24	20	20
10	36	27	22	18	35	27	22	18	26	21	18	18

Fixture Length			Length
T12	T8	T5	
F20T12	F17T8	F14T5	24"
F40T12	F32T8	F28T5	48"
F96T12	F96T8	—	96"

**For Tandem Units:**  
Multiply lamp length above by lamp quantity



max weight= 16lbs/48 32lbs/96"

## Ordering Guide

207				
Series	# of Lamps	Lamp Size	Ballast Type	Options
<b>&amp;S7</b> 2 MG [ ] 3 MA [ ] 4 MA [ ] Vag a^ [ A ] • 22 Vag a^ [ A ] 23 Vag a^ [ A ] • 24A		<b>T8</b> 17 = F17V 25 = F25V 32 = F32V 59A = F59T8 86 = F96T8/HO  <b>T12</b> 15 = F15T12 20 = F20T12 30 = F30T12 40 = F40T12 96 = F96T12 96HO = F96T12/HO	<b>T5</b> 14 = F14T5 21 = 21T5 28 = F28T5  <b>T5HO</b> 24 = F24T5 39 = F39T5 54 = F54T5"	120 = 120V MV = Multivolt E-LW = Electronic .77 BF E-O = Electronic 1.18 BF E-DIM = Dimming Unit  SET LED N = Wired 1 end hot for LED tubes SET LED N/S = Wired 2 ends hot for LED tubes W/LEDIF = LED ballast driven tubes
				<b>EMB</b> [ ] <b>2BAL</b> [ ] <b>OCC-E</b> = External occupancy sensor