

Project:	
Type:	
Catalog #:	



STANDARD



V@/P" • !-æ^Á [~] c^áÁ !æ Áæ [~] áÁ} æ^Á • á • á^Á | Á
 • ^Á Á [• oÁ] { { ^! &æÁ • á^Á } æÁæ á/á • cæ cæ } æÁ | ^Á
 æ] | æææ } • ÉV@Á} áÁ | cæ^Á æá { Á @Á d oÁ æÁ
 { á á { &^ææ &^É

Construction:

- Housing is designed from heavy gauge die formed steel and is finished in baked white enamel or polyester powder coating for maximum durability and reflectivity. Clear acrylic prismatic wrap around diffuser hinges from either side and snaps on and off for easy maintenance.

Electrical

All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request. Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standard. All units are UL certified damp location

Mounting


Wj æ^Á ~ á] ^áÁ æÁ } [& [~ • Áæ áÁQ | • Á | Á
] ^) áæ oÁ | Á ~ !-æ^Á [~] cæ^Á æÁ cæ^Á | ^Á æÁ
 { [~] c^áÁ áææ æ^Á | Á | Á } cæ [~ • Á } É

WARRANTY & LISTINGS

- 5-year warranty of all electronics and housing.
- UL Certified for damp location



DIMENSIONS




Fixture Length			Length
T12	T8	T5	
F20T12	F17T8	F14T5	24"
F40T12	F32T8	F28T5	48"
F96T12	F96T8	—	96"

Coefficients Utilization Zonal Cavity Method

RF	RC	20											
		80%				70%				50%			
RW		70	50	30	10	70	50	30	10	50	30	10	
0		80	80	80	80	78	78	78	78	73	73	73	
1		74	72	68	66	72	69	67	64	65	63	62	
2		68	63	59	55	66	61	58	54	58	55	53	
3		63	56	51	48	61	55	51	47	53	49	46	
4		58	51	45	41	56	49	44	41	47	43	40	
5		53	45	40	35	52	44	39	35	42	38	34	
6		49	41	35	31	48	40	35	31	38	34	30	
7		46	37	31	27	44	36	31	27	35	30	27	
8		42	33	28	24	41	33	27	24	31	27	23	
9		39	30	24	21	38	29	24	21	28	24	20	
10		36	27	22	18	35	27	22	18	26	21	18	

For Tandem Units:
 Multiply lamp length above by lamp quantity



max weight= 16lbs/48 32lbs/96"

Ordering Guide

209 LED	Series	Size	Lumens	Color	Options
&\$9 LED		2 = 2FT 4 = 4FT 6 = 6FT 8 = 8FT	2FT 3166 (17W) 4350 (24W) 5470 (31W) 6452 (39W)	3K 35K 4K 5K	EMB MA (^!*^) & Áææ c 2BAL M/Gæææ á OCC-E = External occupancy sensor FR = Frosted Lens over LED Board
			4FT 3220 (17W) 4480 (24W) 5705 (30W) 6910 (37W) 8640 (48W) 11797 (70W) 13820 (74W) 17280 (96W) 23594 (140W)		
			8FT 3220 (17W) 4480 (24W) 5705 (30W) 6910 (37W) 8640 (48W) 11797 (70W)		

*\$!%\$j ^ck j c^hU [Y^X] a a]b [^ghUbXUF^dYf ^
 z] h fY

*<] [\ Yf^UbX^W gtrca ^i a Yb^dUW^Uf Yg ^
 Uj Uj^UV^Yi dcb^fYei Ygfi

*Call Factory for lumen options of 3FT and 6FT model