

&\$9 Series

Project:	
Туре:	
Catalog #:	

STANDARD



Construction:

 Housing is designed from heavy gauge die formed steel and is finished in baked white enamel or polyester powder coating for maximum durability and reflectivity. Clear acrylic prismatic wrap around diffuser hinges from either side and snaps on and off for easy maintenance.

Electrical

All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request. Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standard. All units are UL certified damp location M 59006648

Mounting

W) ão/ás Á*``ā] ^åÁ ão@Á }[&\[`o Ása) å Á@[/• Á[¦Á]^} åæ) oá[¦Á*`¦-æ&^Á[[`}cā]*ÈŹ @ã Áācc`¦^Á&æ) Ás^Á {[`}c*åÁs) åãçãã`æ||^Á[¦Á&[}cā]`[`•Á`}ÈÁ

Væ))å^{ Áç [Á[, ∙

22

Væ}å^{Áx@2^^Á[,

Væ))å^{ ÁĮٍĭ¦Á[,•

23

24Á

Ordering Guide

28 20 Plan 207 # of Lamps Options Lamp Size Ballast Type Series <u>T8</u> &\$9 T5 120 = 120VEMB MÁ { ^ !* ^ } & Áaæ |æ c 17 = ØFÏ VÌ 25 =ØGÍ VÌ **14** = F14T5 MV = Multivolt 2 MÁGÁ;æ[] 2BAL MÁGÁsæ a cÁ **21** = 21T5 **28** = F28T5 3 MÁHÁpæ{jÁ E-LW = Electronic .77 BF 32 = ØHGVÌ OCC-E = External occupancy sensor 4 MÁ Áæ≩ÍÁ E-O = Electronic 1.18 BF 59Á/Á296tT8 **E-DIM** = Dimming Unit 86= F96T8/HO

<u>T5HO</u> 24 = F24T5

39 = F39T5

54 = F54T5"

<u>T12</u>

15= F15T12

20 = F20T12'

30 = F30T12

40= F40T12

96= F96T12 96HO = F96T12/HO **Small Wrap Around Surface Mount Units**





WARRANTY & LISTINGS



5-year warranty of all electronics and housing.
UL Certified for damp location M 59006648

DIMENSIONS





SET LED N = Wired 1 end hot for LED tubes

W/LEDIF = LED ballast driven tubes

SET LED N/S = Wired 2 ends hot for LED tubes

Fixture Length				
T12	Т8	T5	Length	
F20T12	F17T8	F14T5	24"	
F40T12	F32T8	F28T5	48"	
F96T12	F96T8	-	96"	

For Tandem Units: Multiply lamp length above by lamp quantity

