

1" Deep Undercabinet Unit

Project:	
Type:	
Catalog #:	



STANDARD



The shallowest of all fixtures, this unique 1" deep unit is specially designed for T-5 tubes to be mounted under cabinet with flat, non recessed base. 320 series fixtures are ideal for use in kitchens, hospitals, desk areas, and bathrooms.

Construction:

- Housing is designed from heavy gauge die formed steel and finished in a baked white enamel or polyester powder coating for maximum reflectivity and durability. Lens is extruded white acrylic that snaps on and off for easy relamping.

Electrical

All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request. Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standard. All units are UL certified damp location M 59006648

Mounting



Every fixture is supplied with keyhole slots for easy surface mounting without entering ballast raceway. 1/2" knockouts provided in ends and bottom for supply connection.

WARRANTY & LISTINGS

- 5-year warranty of all electronics and housing.
- UL Certified for damp location M 59006648



DIMENSIONS



Fixture Length

T5	Length
F8T5	12"
F13T5	21"
F14T5	23"
F21T5	35"
F28T5	47"

Ordering Guide

max weight= 6lbs/ 21"

Series	# of Lamps	Lamp Size	Ballast Type	Options
320	1 = 1 Lamp	T5 08 = F8T5 13 = F13T5 14T5 = F14T5 21T5 = F21T5 28T5 = F28T5	120 = 120V MV = Multivolt E-LW = Electronic .77 BF E-O = Electronic 1.18 BF E-DIM = Dimming Unit SET LED N = Wired 1 end hot for LED tubes SET LED N/S = Wired 2 ends hot for LED tubes W/LEDIF = LED ballast driven tubes	O = Grounded Outlet TOG= Toggle Switch ROC = Rocker Switch PULL = Pull chain Switch CP-XE = Cord Exit End CP-XS = Cord Exit Side CP-XB = Cord Exit Base