

## Chrome Covered Bathroom Wall Unit

Project:	
Type:	
Catalog #:	



### STANDARD



This covered chrome channel can be mounted both vertically and horizontally and comes in a variety of sizes for a wide range of uses. It is ideal for use in bathrooms, kitchens, powder rooms, under cabinets, or any area where high quality and low cost lighting is preferred.

### Construction:

- Housing is designed from heavy gauge die formed steel and plated in a high polished chrome for high grade appearance. Off and on switch is standard in end plate. Snap in grounded convenience outlet is available upon request. End plates are secured to fixture by acorn nuts. Lens is extruded white acrylic.

### Electrical

All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request. Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standard. All units are UL certified damp location M 59006648

### Mounting


Holes and knockouts are provided in units for surface or wall mounting either vertically or horizontally.

### WARRANTY & LISTINGS


- 5-year warranty of all electronics and housing.
- UL Certified for damp location M 59006648



### DIMENSIONS



Fixture Length		
T12	T8	Length
F15T12	---	18 1/2"
F20T12	F17T8	24 1/2"
F30T12	F25T8	36 1/2"
F40T12	F32T8	48 1/2"



### Ordering Guide

Max weight = 13lbs / 48"

Series	# of Lamps	Lamp Size	Ballast Type	Options	
1P	1 = 1 Lamp	<b>T8</b> 17 = F17T8 25 = F25T8 32 = F32T8*  <b>T12</b> 14 = F14T12 15 = F15T12 20 = F20T12 30 = F30T12 40 = F40T12	<b>T5</b> 14 = F14T5 21 = F21T5 28 = F28T5  <b>T5HO</b> 24 = F24T5 39 = F39T5* 54 = F54T5	MV = Multivolt 120 = 120 Volt 277 = 277 Volt  SET LED N = Wired 1 end hot for LED tubes SET LED N/S = Wired 2 ends hot for LED tubes W/LEDIF = ballast driven LED tubes	O = Grounded Outlet TOG = Toggle Switch ROC = Rocker Switch PULL = Pull Switch EMB = Emergency Ballast 3WAY = 3 Way system