

Project:	
Type:	
Catalog #:	



STANDARD



This fully weatherproof T5 or T8 unit is designed for use in areas of wet location. Designed to withstand direct contact with rain this unit is corrosion resistant and waterproof. This unit is ideal in areas such as car washes, store fronts, parking garages, kitchens, and chemical plants. Vapor Tite unit is capable of being hosed down for easy cleanin

Construction:

- Exterior housing is designed for single piece injection molded fiberglass/plastic combination blend. Neoprene gasket and stainless steel pressure locks ensure waterproof seal. Interior gear tray is heavy gauge die formed steel which hinges to allow electrical raceway access while remaining attached to luminaire housing during installation and maintenance.

ELECTRICAL

All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request. Fixtures meet requirements for UL Luminare Standard # 1598. All units comply with National Energy Standard. All units are UL certified damp and wet location M 59006648

Mounting



Vapor Tite Unit available with an stainless steel external hanging bracket. VT Series is watertight and must be drilled and sealed for each surface mounting or chain hanging application.

WARRANTY & LISTINGS

- 5-year warranty of all electronics and housing.
- UL Certified for damp and wet location M 59006648



DIMENSIONS



Fixture Length

T8	T5	T5HO	Length
F32T8	F28T5	F54T5HO	50"

RF	20									
	80%				70%			50%		
RC	70	50	30	10	70	50	30	10	50	30
0	109	109	109	109	107	107	107	107	101	101
1	98	93	89	84	95	91	86	83	86	83
2	89	80	73	67	86	78	72	66	74	69
3	81	70	62	56	78	68	61	55	65	59
4	74	62	53	47	71	60	52	46	57	51
5	67	54	45	39	65	53	45	38	50	43
6	61	48	39	33	59	47	39	33	45	38
7	56	43	35	29	54	42	34	28	40	33
8	52	39	30	25	50	38	30	24	36	29
9	48	35	27	21	46	34	25	21	32	25
10	44	31	24	19	43	31	23	18	30	23

Ordering Guide

Max weight = 20lbs / 48"

CIT4 Series	# of Lamps	Lamp Size	Ballast Type	Options	
CIT4	4= 4 Lamp 5= 5 lamp 6= 6 lamp	T8 17 = F17V 32 = F32V T12 20 = F20T12" 40 = F40T12	T5 14 = F14T5 28 = F28T5 T5HO 24 = F24T5 54 = F54T5*	120 = 120V MV = Multivolt E-LW = Electronic .77 BF E-O = Electronic 1.18 BF E-DIM = Dimming Unit SET LED N = Wired 1 end hot for LED tubes SET LED N/S = Wired 2 ends hot for LED tubes W/LEDIF = LED ballast driven tubes	EMB MA (A)* (A) & A (A) (A) 2BAL (A) (A) (A) (A) REFS = Silver Reflector OCC-E = External Occupancy Sensor OCC-I = Internal Occupancy Sensor BILEVEL = Bi-level system SS = Stainless Steel Latch POLY = Polycarb lens