

Project:	
Type:	
Catalog #:	



STANDARD



This "Classroom" surface mounted wrap around unit is designed for use in most commercial, residential, and institutional type applications. The unit provides maximum light output and is available in 1, 2, or 3 lamp options with or without a specular mirror.

Construction:

- Housing is designed from heavy gauge die formed and is finished in baked white enamel or polyester powder coating for maximum durability and reflectivity. Clear acrylic prismatic wrap around diffuser snaps on and off for easy maintenance.

Electrical

All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request. Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standard. All units are UL certified damp location

Mounting


Unit is equipped with knockouts and holes for pendant or surface mounting. This Fixture can be mounted individually or continuous run.

WARRANTY & LISTINGS

- 5-year warranty of all electronics and housing.
- UL Certified for damp location



DIMENSIONS




Fixture Length			
T12	T8	T5	Length
F40T12	F32T8	F28T5	48"
F96T12	F96T8	---	96"

For Tandem Units:
Multiply lamp length above by lamp quantity

RF	20									
RC	80%		70%		50%					
RW	70	50	30	70	50	30	10	50	30	10
0	80	80	80	80	78	78	78	73	73	73
1	74	72	68	68	69	67	64	65	63	62
2	68	63	59	66	61	58	54	58	55	53
3	63	56	51	64	55	51	47	53	49	46
4	58	51	45	66	49	44	41	47	43	40
5	53	45	40	63	44	39	35	42	38	34
6	49	41	35	68	40	35	31	38	34	30
7	46	37	31	67	36	31	27	35	30	27
8	42	33	28	64	33	27	24	31	27	23
9	39	30	24	68	29	24	21	28	24	20
10	36	27	22	68	27	22	18	26	21	18

1 Tube Photometric Curve



max weight= 18lbs/48" 35lbs/96"

Ordering Guide

ECW LED

Series

ECW LED

Size

- 2 = 2FT
- 4 = 4FT
- 6 = 6FT
- 8 = 8FT

Lumens

- 2FT**
- 3166 (17W)
- 4350 (24W)
- 5470 (31W)
- 6452 (39W)
- 4FT**
- 3220 (17W)
- 4480 (24W)
- 5705 (30W)
- 6910 (37W)
- 8640 (48W)
- 11797 (70W)
- 8FT**
- 3220 (17W)
- 4480 (24W)
- 5705 (30W)
- 6910 (37W)
- 8640 (48W)
- 11797 (70W)

Color

- 3K
- 35K
- 4K
- 5K

Options

- EMBM = { } & { } c
- REF-S = Silver Reflector
- OCC-I = Internal Occupancy Sensor
- OCC-E = External Occupancy Sensor
- FR = Frosted Lens over LED Board

*Call Factory for lumen options of 3FT and 6FT model

*Call Factory for lumen options of 3FT and 6FT model

*Call Factory for lumen options of 3FT and 6FT model