

Project	
Type	
Catalog #	

Overview

- 10W
- 120V Input
- Phase Control Dimming



Standard



HOUSING & CONSTRUCTION

- Highly diffused plastic lens for even light distribution
- Steel housing
- Standard finish: premium powder-coated in white
- Sleek 1" profile

LEDS

- Manufacturer: Philips Lumileds
- Rated life: 50,000 hours
- Color temperature: 3000K; other color temperatures available for custom orders

DRIVER

- 12W LED driver for 12"-24" fixture models; 25W LED driver for 36"-48" fixture models
- 120V input
- UL Recognized Class 2 power supply
- Type 1 Outdoor, suitable for dry and damp locations

DIMMING

- Phase control dimming
- Suitable for use with TRIAC dimmers

WIRING & SWITCHING

- Convertible 120V direct wire input; knockouts provided for multiple input configurations

PACKAGING


Contents in each fixture carton:

- (1) LED fixture
- (2) Mounting screws
- (3) Wire nuts
- (1) Die-cast coupler
- (1) Optional on/off rocker switch
- Instruction sheet

WARRANTY

- 5 years

PHYSICAL SPECIFICATIONS



Length	Width	Height
18"	2.75"	1"

Catalog Number	Wattage	CCT	CRI	Total Lumens	Efficacy
UC-LED-18-DW-830	10W	3000K	>80	675	68 lm/W