

OD LED Series

Outdoor Billboard Sign Units

Project: Type: Catalog #:

STANDARD







This billboard unit provides high light levels with even distribution, for spot lighting. The unit is weather resistant and suitable for most outdoor applications.

Construction:

· Housing is made of heavy gauge extruded aluminum with die cast end plates and splice box fittings. Housing interior is finished in a baked enamel finish for maximum reflectivity and durability. Splice box is threaded for 3/4" conduit and contains adjusting screws for housing. Lens is clear smooth slide-on acrylic that resists yellowing.

Electrical

All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request. Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standard. All units are UL certified damp and wet location


Mounting

Units are designed to be conduit mounted either individually, tandem, or in a continuous run

WARRANTY & LISTINGS

- 5-year warranty of all electronics and housing.
- UL Certified for wet location

DIMENSIONS




Fixture Length

I IXture Length		
# of Lamps	T5HO	Length
1 or 2	F54T5HO	53"
TANDEM		
Single or Double	F54T5HO	101"

For Tandem Units Multiply Unit above by 2

Ordering Guide



*Call Factory for lumen options of 6FT models

Lumens

4FT	<u>8FT</u>
3220 (17W)	3220 (17W)
4480 (24W)	4480 (24W)
5705 (30W)	5705 (30W)
6910 (37W)	6910 (37W)
8640 (48W)	8640 (48W)
11797 (70W)	11797 (70W)
, ,	13820 (74W)
	17280 (96W)
	23594 (140W

Color 3K 35K 4K 5K

Options

EMB MÁY{ ^|* ^} & Áaæ|æ oÁ FR = Frosted lens over LED Boards

max weight= 11lbs/53" 15lbs/101"