

LED OUTDOOR WALL MOUNT SERIES ROTATABLE WALL PACK / BULKHEAD

LED BUILT-IN

SWITCH

 \bigcirc Collor Selectab

> SWITCH \bullet

| | PROJECT | |
|--|-----------|--|
| | ТҮРЕ | |
| | CATALOG # | |

LED Outdoor Wall Mount Series Rotatable Wall Pack

LED Rotatable Wall Pack fixtures are designed to provide ample outdoor illumination with an adjustable light bank allowing you to direct the light for optimal coverage. The weather-resistant aluminum body is finished in black and houses a durable polycarbonate lens. Ideal for security and general purpose lighting along the perimeter of buildings, entryways or anywhere extra lighting is needed. For use with 100-277 volt electrical service. UL Listed for wet location installation and DLC Listed for guality and efficiency.





Rotate 270 Degrees to allow you to customize your range of light





Aluminum Body **Clear Lens Black Finish** 70 CRI

Application



Options

[•••]

| ltem# | Description | Watt | Lumen | Volt | Color Temp | Hours | Features | Dimension(in) |
|-------|--------------|------|-------|---------|------------|-------|------------|-----------------------|
| 97087 | RWP/40W/50K | 40 | 5200 | 100-277 | 5000K | 50000 | WL,DLC | 5.3(h) 5.4(w) 9.2(d) |
| 97088 | RWP/60W/50K | 60 | 7800 | 100-277 | 5000K | 50000 | WL,DIM,DLC | 9.4(h) 5.9(w) 10.0(d) |
| 97095 | RWP/80W/3SCT | 80 | 10640 | 100-277 | 30/40k/50K | 50000 | WL,DIM,DLC | 5.3(h) 8.7(w) 9.2(d) |

LED Outdoor Wall Mount Series Bulkhead









Aluminum Body Frosted Lens Textured Black Finish 80 CRI

| | | B Round | | Applicat | Application | | Landscape Commercial Residential | | |
|---------|----------------|---------|-------|----------|-------------|-------|----------------------------------|----------------|--|
| ltem# | Description | Watt | Lumen | Volt | Color Temp | Hours | Features | Dimension(in) | |
| Cut-Off | | | | | | | | | |
| 81309 | BOF/12W/30K/BK | 12 | 600 | 120 | 3000K | 50000 | WL,DIM | 3.6(w) 11.0(d) | |
| Round | | | | | | | | | |
| 81384 | BH/20W/3SCT/BK | 20 | 1000 | 120 | 30K/40K/50K | 50000 | WL,DIM | 3.6(w) 11.0(d) | |

Specifications may change without notice. We are not responsible for any typ

