

Project:	
Type:	
Catalog #:	



STANDARD



This covered wall unit is designed to provide maximum lumen output in areas such as hallways, bathrooms, kitchens, stairways, and hospitals. An assortment of options in either single or double lamp allows this utility wall and surface mounted unit to satisfy a variety of lighting needs.

Construction:

- Housing is designed from heavy gauge die formed steel and finished in either baked white enamel or polyester powder coating. Socket plate is riveted to housing adding to the structural support of the fixture. Lens is extruded white acrylic. End plates are attached by acorn nuts and secure the lens to the fixture.

Electrical

All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request. Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standard. All units are UL certified damp location M 59006648

Mounting



Unit is equipped with holes and 7/8" knockouts in housing for surface mounting. Fixture may be mounted individually or with optional joiner bands may be used in a continuous run.

WARRANTY & LISTINGS

- 5-year warranty of all electronics and housing.
- UL Certified for damp location



DIMENSIONS



Fixture Length			
T12	T12HO	T8	Length
F15T12	---	---	18"
F20T12	---	F17T8	24"
F30T12	---	F25T8	36"
F40T12	F48T12HO	F32T8	48"

Ordering Guide

Max weight = 12lbs / 48"

555 - LED

Series

555- LED

Size

18 = 18"
2 = 2FT
3 = 3FT
4 = 4FT

Lumens

2FT
3166 (17W)
4350 (24W)
5470 (31W)
6452 (39W)

Color

3K
35K
4K
5K

Options

EMBM = EMBM & Acorn Nut
REFS = Silver Reflector
OCC-E = External Occupancy Sensor
OCC-I = Internal Occupancy sensor
BI-LEV = Bi-level dimming system
O = grounded outlet
TOG = Toggle Switch
PULL = Pull chain switch
NL = Night Light
3WAY = 3 way system
PRIS = Prismatic lens
DL = Down light only
POLY = Polycarb lens
FR = Frosted lens over LED boards
VP = Vandal Proof

*Call Factory for lumen options of 18" and 3FT models

*Call Factory for lumen options of 18" and 3FT models

*Call Factory for lumen options of 18" and 3FT models

4FT
3159 (20W)
4480 (30W)
5684 (42W)
6318 (40W)
8960 (60W)
11368 (84W)