

PROJECT	
TYPE	
CATALOG #	



24W, 120–277V Input, 0–10V Dimming

APPLICATION

Used for commercial recessed ceiling applications



PRODUCT FEATURES

- Architectural grade center basket volumetric design
- Powered by 0–10V dimming LED drivers
- Smooth diffused lens for even appearance
- 0–10V dimming, 10% minimum
- Compatible with emergency backups
- Compatible with occupancy sensors
- Ambient operating temperature: –20°C/–4°F to 50°C/122°F
- UL Listed 1598: Suitable for dry and damp locations
- THD: <20%
- PF: >0.95
- LED chip lifetime: L70 >100,000 hrs @ 25°C/77°F ambient fixture temp.
- Low optical flicker

PRODUCT SPECIFICATIONS

Catalog Number	Color Temperature	Nominal Length	Input Voltage	Wattage	CRI	Lumen Output	Efficacy
CBT-LED-22A-24-835-P	3500K	2 ft. × 2 ft.	120–277V	24W	>82.0	2,975 L	124 lm/W
CBT-LED-22A-24-840-P	4000K	2 ft. × 2 ft.	120–277V	24W	>82.0	3,025 L	126 lm/W
CBT-LED-22A-24-850-P	5000K	2 ft. × 2 ft.	120–277V	24W	>82.0	3,050 L	128 lm/W

PHYSICAL SPECIFICATIONS

