

# CBT-LED-24A-38-8XX-9

## 2' X 4' LED CENTER BASKET FIXTURE

PROJECT	
TYPE	
CATALOG #	



38W, 120–277V Input, 0–10V Dimming

### APPLICATION

Used for commercial recessed ceiling applications



### PRODUCT FEATURES

- Architectural grade center basket volumetric design
- Powered by 0–10V dimming LED drivers
- Smooth diffused lens for even appearance
- 0–10V dimming, 10% minimum
- Compatible with emergency backups
- Compatible with occupancy sensors
- Ambient operating temperature:  $-20^{\circ}\text{C}/-4^{\circ}\text{F}$  to  $50^{\circ}\text{C}/122^{\circ}\text{F}$
- UL Listed 1598: Suitable for dry and damp locations
- THD:  $<20\%$
- PF:  $>0.95$
- LED chip lifetime:  $L70 >100,000$  hrs @  $25^{\circ}\text{C}/77^{\circ}\text{F}$  ambient fixture temp.
- Low optical flicker

### PRODUCT SPECIFICATIONS

Catalog Number	Color Temperature	Nominal Length	Input Voltage	Wattage	CRI	Lumen Output	Efficacy
CBT-LED-24A-38-835-P	3500K	2 ft. x 4 ft.	120–277V	38W	$>82.0$	4,720 L	124 lm/W
CBT-LED-24A-38-840-P	4000K	2 ft. x 4 ft.	120–277V	38W	$>82.0$	4,790 L	126 lm/W
CBT-LED-24A-38-850-P	5000K	2 ft. x 4 ft.	120–277V	38W	$>82.0$	4,825 L	128 lm/W

### PHYSICAL SPECIFICATIONS

