


Project:	
Type:	
Catalog #:	

GIMBAL RECESSED DOWNLIGHT
CCT SELECTABLE ROUND & SQUARE
2", 3" & 4"



Project:	
Type:	
Catalog #:	

SPECIFICATIONS

ELECTRICAL

		DESCRIPTION	POWER	INPUT VOLTS	DIMMABLE	EFFICACY	FREQUENCY	WATT REPLACEMENT	LIFETIME
2"	RD	23236	LED5W/DL2/GB/5CCT/FL	5	120V	YES	80	50/60Hz	50,000
		23241	LED8W/DL3/GB/3CCT/RD/BK	8	120V	YES	75	50/60Hz	50,000
3"	SQ	23246	LED8W/DL3/GB/3CCT/FL	8	120V	YES	75	50/60Hz	50,000
		23250	LED8W/DL3/GB/3CCT/SQ	8	120V	YES	75	50/60Hz	50,000
4"	RD	23255	LED11W/DL4/GB/3CCT/RD	11	120V	YES	91	50/60Hz	50,000
		23257	LED11W/DL4/GB/3CCT/RD/BK	11	120V	YES	91	50/60Hz	50,000

PHOTOMETRIC

GENERAL

MODEL	COLOR (CCT)	TEMP	LUMEN	FLOOD	CRI	FINISH	DAMP LOCATION	COST/YR	ETL LISTED	ENERGY STAR
23236	2700K/3000K/3500K/4000K/5000K	WARM/SOFT/NATURAL/COOL/BRIGHT	400	40°	80	WHITE	YES	\$ 0.60	YES	YES
23241	3000K/4000K/5000K	SOFT/COOL/BRIGHT	600	40°	80	BLACK	YES	\$ 0.96	YES	
23246	3000K/4000K/5000K	SOFT/COOL/BRIGHT	600	40°	80	WHITE	YES	\$ 0.96	YES	YES
23250	3000K/4000K/5000K	SOFT/COOL/BRIGHT	600	40°	80	WHITE	YES	\$ 0.96	YES	YES
23255	3000K/4000K/5000K	SOFT/COOL/BRIGHT	1000	40°	80	WHITE	YES	\$ 1.32	YES	YES
23257	3000K/4000K/5000K	SOFT/COOL/BRIGHT	1000	40°	80	BLACK	YES	\$ 1.32	YES	

DIMENSIONS

