

PROJECT	
TYPE	
CATALOG #	



### Complete Compact 155W LED High Bay Fixture; 120–277V Input

#### PRODUCT FEATURES

- Architectural grade compact design
- Designed to accept easy screw-in installation of optional sensors via 1/2" threaded receptacle in driver cover
- Compatible with emergency LED drivers; mounting kit required (sold separately)
- Powered by 0–10V dimming LED drivers with 12V Aux
- Frosted lens eliminates glare
- V-hook and chain mounting accessories included
- UL Listed 1598: Suitable for dry and damp locations
- Ambient operating temperature:  $-20^{\circ}\text{C}/-4^{\circ}\text{F}$  to  $50^{\circ}\text{C}/122^{\circ}\text{F}$
- THD:  $<20\%$
- PF:  $>0.90$
- LED chip lifetime: L70  $>100,000$  hrs @  $25^{\circ}\text{C}/77^{\circ}\text{F}$  ambient fixture temp.




#### PERFORMANCE SPECIFICATIONS


CATALOG NUMBER	NOMINAL LENGTH	INPUT VOLTAGE	CCT	WATTAGE	LUMEN OUTPUT	EFFICACY	CRI	POWER FACTOR	LIFETIME
HB-LED-2-155-840-P /G2	2 ft.	120–277V	4000K	155W	23,250	150 lm/W	$>80.0$	$>0.90$	50,000 hrs
HB-LED-2-155-850-P /G2	2 ft.	120–277V	5000K	155W	23,405	151 lm/W	$>80.0$	$>0.90$	50,000 hrs

#### PHOTOMETRIC SPECIFICATIONS

##### ISOCANDELA PLOT



##### POLAR CANDELA DISTRIBUTION




##### ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
0–30	6,673.5	30.30%
0–40	10,833.6	49.10%
0–60	18,337.7	83.20%
60–90	3,649.0	16.50%
70–100	1,380.5	6.30%
90–120	17.5	0.10%
0–90	21,986.7	99.70%
90–180	62.8	0.30%
0–180	22,049.5	100%

PROJECT	
TYPE	
CATALOG #	

### PHYSICAL SPECIFICATIONS



### ORDERING INFORMATION

ORDER CODE	PACK QTY.	UPC	EASY CODE
HB-LED-2-155-840-P /G2	1	843654136905	DCG-13
HB-LED-2-155-850-P /G2	1	843654136912	ONY-90