

Project:	
Type:	
Catalog #:	



STANDARD



This cost effective right angle strip is ideal for use in all residential, commercial, and institutional areas where clearance and spacing is a problem and general lighting is desired.

Construction:

- This unit is designed from heavy gauge die formed steel and is finished in baked white enamel or polyester powder coating for maximum durability and reflectivity. Snap on sockets, end plates, and ballast cover allow for tool free assembly.

WARRANTY & LISTINGS

- 5-year warranty of all electronics and housing.
- UL Certified for damp location




Electrical

All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request. Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standard. All units are UL certified damp location

Mounting

Unit is equipped with knockouts and holes for pendant or surface mounting. This fixture can be mounted individually or in continuous run. 7/8" knock out is provided in end plate for conduit connector.

DIMENSIONS



Fixture Length

T12	T8	T5	T5HO	Length
F14T12	---	---	---	15"
F15T12	---	---	---	18"
F20T12	F17T8	F14T5	F24T5HO	24"
F30T12	F25T8	F21T5	F39T5HO	36"
F40T12	F32T8	F28T5	F54T5HO	48"

For Tandem Units:
Multiply lamp length above by lamp quantity

Max Weight = 9lbs/ 48"

Ordering Guide

RA-LED

Series	Size	Lumens	Color	Options
RA-LED	2 = 2FT 4 = 4FT 6 = 6FT 8 = 8FT	2FT 3166 (17W) 4350 (24W) 5470 (31W) 6452 (39W) 4FT 3220 (17W) 4480 (24W) 5705 (30W) 6910 (37W) 8640 (48W) 11797 (70W)	8FT 3220 (17W) 4480 (24W) 5705 (30W) 6910 (37W) 8640 (48W) 11797 (70W) 13820 (74W) 17280 (96W) 23594 (140W)	3K 35K 4K 5K EMB (External Occupancy Sensor) OCC-E = External Occupancy Sensor OCC-I = Internal Occupancy sensor BI-LEV= Bi-level dimming system O = grounded outlet TOG = Toggle Switch PULL= Pull chain switch C+P = Cord & plug ASY= Asymmetrical Reflector 3WAY = 3 way system FR= Frosted Lens over LED boards

*Call Factory for lumen options of 3FT and 6FT models

*Call Factory for lumen options of 3FT and 6FT models

*Call Factory for lumen options of 3FT and 6FT models