

S-LED-4-18-8XX-P

4' LED STRIP FIXTURE

PROJECT	
TYPE	
CATALOG #	



18W, 120-277V Input, 0-10V Dimming

PRODUCT FEATURES

- Powered by 0-10V dimming LED drivers
- Smooth diffused lens for an even appearance
- 0-10V dimming, 10% minimum
- Compatible with emergency LED drivers
- Compatible with 480-277V step down transformers
- Compatible with occupancy sensors
- Ambient operating temperature: -20°C/-4°F to 50°C/122°F
- UL Listed 1598: Suitable for dry and damp locations
- THD: <20%
- Power factor > 0.95
- L70 >50,000 hours



AVAILABLE MODIFICATIONS (WITH VOLUME ORDER)


- Lumen targets
- Frame colors

PERFORMANCE SPECIFICATIONS

Catalog Number	Color Temp	Nominal Length	Input Voltage	Wattage	CRI	Lumen Output	Efficacy
S-LED-4-18-835-P	3500K	4'	120-277V	18W	>82	2290	127 lm/W
S-LED-4-18-840-P	4000K	4'	120-277V	18W	>82	2320	129 lm/W
S-LED-4-18-850-P	5000K	4'	120-277V	18W	>82	2340	130 lm/W

PROJECT	
TYPE	
CATALOG #	


PHOTOMETRIC SPECIFICATIONS



Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	496.4	21.9%
0-40	814.4	35.9%
0-60	1,464.6	64.6%
60-90	603.1	26.6%
70-100	422.8	18.6%
90-120	166.2	7.3%
0-90	2,067.6	91.1%
90-180	200.9	8.9%
0-180	2,268.6	100%

PHYSICAL SPECIFICATIONS



ORDERING INFORMATION

Catalog Number	Packaging Style	Quantity	Item Status
S-LED-4-18-835-P	Carton Pack	1	Active
S-LED-4-18-840-P	Carton Pack	1	Active
S-LED-4-18-850-P	Carton Pack	1	Active