

LED OUTDOOR SECURITY FLOOD LIGHT MOTION SENSOR

PROJECT	
TYPE	
CATALOG #	

LED Outdoor Security Flood Light

Motion Sensor











Wall Mount Floodlight fixtures provide ample illumination for all outdoor spaces. Dual heads can be adjusted individually to optimize coverage area. Built-in motion sensor activates lights when movement is detected. Long life, LED technology built-in means no bulbs to replace and up to 35,000 hours of maintenance-free service. ETL Listed for wet location installation and IP65 rated.

Plastic Body
Clear Lens
Black Finish
Built-in Photocell & Motion Sensor
80 CRI







Application









ltem#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
2 Head Rou	und Style 1							
A 88907	OSF/R/MS/20W/50K/BK	20	1800	120	5000K	35000	WL	9.3(h) 6.3(w) 7.6(d)
B 88909	OSF/R/MS/20W/50K/WH	20	1800	120	5000K	35000	WL	9.3(h) 6.3(w) 7.6(d)
2 Head Rou	und Style 2	•	•	•	•	•	•	•
88906	OSF/R/MS/20W/30K/BK	20	1800	120	3000K	35000	WL	9.3(h) 6.3(w) 7.6(d)
88908	OSF/R/MS/20W/30K/WH	20	1800	120	3000K	35000	WL	9.3(h) 6.3(w) 7.6(d)
2 Head Squ	uare	•	•	•	•	•	•	•
88911	OSF/S/MS/24W/30K/BK	24	2400	120	3000K	35000	WL	11.9(h) 6.1(w) 5.9(d)
88912	OSF/S/MS/24W/50K/BK	24	2400	120	5000K	35000	WL	11.9(h) 6.1(w) 5.9(d)

Outdoor Security Flood Light





120 volts
Medium (E26) Base
Uses PAR38 Bulb(s)
UL Listed

PAR38
Med E26

Application

Bulb Suggestion

Bulb Suggestion

All

PAR38
Med E26

Application

Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
04918	PL2H/WH	White	-	2	60	4.3(h) 4.3(w) 8.5(d)

Specifications may change without notice.
We are not responsible for any typographical errors

