

LED CEILING SEMI FLUSH MOUNT DOUBLE BAND TRIM

PROJECT	
TYPE	
CATALOG #	



Steel & Acrylic Body
White Lens
Brushed Nickel / Oil Rubbed Bronze Finish
80 CRI

Options

5
Year
Warranty



See Components list page for detail

Application



These easy to install, dimmable fixtures have energy-efficient LED technology built-in, so there are no bulbs to replace. The output is a bright, flicker-free 1050 lumen. These tunable fixtures feature innovative technology that allows you to choose the color temperature at the time of installation. Select 3000K Warm White, 4000K Cool White, or 5000K Super White depending on your preference using a switch located on the back. Energy Star Certified and may qualify for state and local rebates.

LED
BUILT-IN



A Brushed Nickel



B Oil Rubbed Bronze

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A 87783	DC012/P/BN/15W/SCT LFX/	15	1050	120	30K/40K/50K	50000	DL,DIM	9.0(w) 12.0(d)
B 87784	DC012/P/ORB/15W/SCT	15	1050	120	30K/40K/50K	50000	DL,DIM	9.0(w) 12.0(d)

LED 15-inch semi flush mount ceiling fixtures are designed for years of maintenance-free service. The brushed nickel finish highlights the stylish and clean appearance that will complement any decor. These easy to install, dimmable fixtures have energy efficient LED technology built-in so there are no bulbs to replace. Ideal for offices, hotel rooms, bedrooms, bathrooms, kitchens, dining areas, entryways or anywhere downlights are needed. They are also UL Listed for damp location installation. With a life span of up to 50,000 hours they are an ideal, no maintenance solution for both residential and commercial installations. ETL Listed for damp location installation.

Steel & Acrylic Body
Acrylic Lens
Brushed Nickel / Oil Rubbed Bronze Finish
80 CRI

5
Year
Warranty

Application



LED Ceiling Semi Flush Mount Solid Band Trim

LED
BUILT-IN



A Brushed Nickel



B Oil Rubbed Bronze

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A 81305-SU	MPM/15"/30W/SCT/SN LFX/	30	1950	120	30K/40K/50K	50000	DL,DIM	9.0(w) 15.0(d)
B 81312-SU	MPM/15"/30W/30K/ORB	30	1950	120	3000K	50000	DL,DIM	9.0(w) 15.0(d)

DIM = Dimmable

DL = Rated Damp Location

WL = Rated Wet Location

DLC = Design Lights Consortium

ES = Energy Star