

Project:	
Type:	
Catalog #:	



STANDARD



This cost effective side mount strip light is ideal for use in all residential, commercial and industrial areas where clearance is a problem and general lighting is desired.

Construction:

- This unit is designed from heavy gauge die formed steel and is finished in baked white enamel or polyester powder coating for maximum durability and reflectivity. Snap on sockets, ends, and ballast cover allow for tool free assembly

Electrical

All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request. Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standard. All units are UL certified damp location M 59006648

Mounting

Unit is equipped with knockouts and holes for pendant or surface mounting. This fixture can be mounted individually or in continuous run. 7/8" knock out is provided in end plate for conduit connector.

WARRANTY & LISTINGS

- 5-year warranty of all electronics and housing.
- UL Certified for damp location M 59006648



DIMENSIONS



Fixture Length


T12	T8	T5	T5HO	Length
F14T12	---	---	---	15"
F15T12	---	---	---	18"
F20T12	F17T8	F14T5	F24T5HO	24"
F30T12	F25T8	F21T5	F39T5HO	36"
F40T12	F32T8	F28T5	F54T5HO	48"

For Tandem Units:

Multiply lamp length above by lamp quantity

Coefficients Utilization Zonal Cavity Method

RF	20										
	80%				70%				50%		
RC	70	50	30	10	70	50	30	10	50	30	10
0	102	102	102	102	95	95	95	95	80	80	80
1	92	88	83	80	85	81	77	74	60	65	63
2	84	76	70	64	77	70	65	60	59	55	51
3	76	67	59	53	70	61	55	50	52	47	43
4	69	59	51	45	64	54	47	42	46	41	36
5	63	52	51	45	58	48	41	35	41	35	31
6	58	46	38	32	53	43	35	30	36	30	26
7	53	41	33	28	49	38	31	26	33	27	23
8	49	37	29	24	45	34	27	23	29	24	20
9	45	33	26	21	42	34	24	20	26	21	17
10	42	30	23	18	39	28	22	17	24	19	15



Max Weight = 9lbs/ 48"

Ordering Guide

Series	# of Lamps	Lamp Size	Ballast Type	Options	
SM	1 = 1 Lamp 2 = Tandem One row 21 22	T8 17 = F17V1 25 = F25V1 32 = F32V1 T12 15 = F15T12 20 = F20T12" 30 = F30T12 40 = F40T12	T5 14 = F14T5 21 = 21T5 28 = F28T5 T5HO 24 = F24T5 39 = F39T5 54 = F54T5"	120 = 120V MV = Multivolt E-LW = Electronic .77 BF E-O = Electronic 1.18 BF E-DIM = Dimming Unit SET LED N = Wired 1 end hot for LED tubes SET LED N/S = Wired 2 ends hot for LED tubes W/LEDIF = LED ballast driven tubes	EMB 2BAL OCC-E = External Occupancy Sensor OCC-I = Internal Occupancy sensor BI-LEV= Bi-level dimming system O= grounded outlet TOG= Toggle Switch PULL= Pull chain switch C+P = Cord & plug 3WAY = 3 way system