

LED CEILING FLUSH MOUNT

PREMIUM DESIGN / MOTION CLOSET LIGHT

| | |
|-----------|--|
| PROJECT | |
| TYPE | |
| CATALOG # | |

LED Ceiling Flush Mount

Premium Design



7" Emergency Battery

81269-SU Emergency Battery

Energy efficient Sunlite LED ceiling fixtures are designed for years of maintenance-free service. These surface mount mini downlights have a slim and simplistic design with brushed nickel trim that fits perfectly into any modern setting. These easy to install, dimmable fixtures have energy efficient LED technology built-in so there are no bulbs to replace. Ideal for closets, hallways, stairways, entryways, storage areas, basements, or anywhere downlight is needed. They are also ETL Listed for damp location installation. With a life span of up to 50,000 hours they are an ideal, no maintenance solution for both residential and commercial installations.

Aluminum & Acrylic Body
White Lens
Bronze / White Finish
90 CRI

5
Year
Warranty



| Item# | Description | Watt | Lumen | Volt | Color Temp | Hours | Features | Dimension(in) |
|---------------------------|------------------------------|------|-------|------|---------------------|-------|----------|----------------------|
| Round 5",7",9",12" | | | | | | | | |
| 81282-SU | LFX/MP/5R/10W/E/D/SCT/WH | 10 | 600 | 120 | 30K/40K/50K | 50000 | DL,DIM | 0.6(w) 5.5(d) |
| 81284-SU | LFX/MP/7R/15W/E/D/SCT/WH | 15 | 900 | 120 | 30K/40K/50K | 50000 | DL,DIM | 0.6(w) 7.4(d) |
| 81286-SU | LFX/MP/9R/18W/E/D/SCT/WH | 18 | 1100 | 120 | 30K/40K/50K | 50000 | DL,DIM | 0.6(w) 9.0(d) |
| 81289-SU | LFX/MP/12R/22W/CRI90/5SCT/WH | 22 | 1450 | 120 | 27K/30K/35K/40K/50K | 50000 | DL,DIM | 0.5(w) 11.75(d) |
| Square 5",9" | | | | | | | | |
| 81283-SU | LFX/MP/5S/10W/E/D/SCT/WH | 10 | 600 | 120 | 30K/40K/50K | 50000 | DL,DIM | 0.6(h) 4.4(d) |
| 81287-SU | LFX/MP/9S/18W/E/D/SCT/WH | 18 | 1100 | 120 | 30K/40K/50K | 50000 | DL,DIM | 0.6(h) 9.0(w) 9.0(d) |

LED Ceiling Flush Mount

Motion Closet Light



On/Off / Bi-Level Sensor



SCT Switch

Sunlite's color selectable mini panel fixture with motion sensor, allows for selecting the light temperature to match a wide range of applications while saving even more energy by illuminating only when needed. The color selectable switch placed on the fixture's side, allows the user to choose between five white color temperatures, ranging from 2700K to 5000K. The Infrared motion sensor located on the fixture, helps save even more energy by either dimming the light output (bi-level) or turning off (on/off) when no motion is detected. This feature can be disabled by simply switching to "off."

Plastic Body
White Lens
White Finish
Built-in Bi-Level Motion Sensor
90 CRI

5
Year
Warranty



| Item# | Description | Watt | Lumen | Volt | Color Temp | Hours | Features | Dimension(in) |
|----------|-----------------------|------|-------|------|---------------------|-------|-----------|----------------|
| 81325-SU | LFX/MP/5R/12W/MS/SCT | 12 | 700 | 120 | 27K/30K/35K/40K/50K | 50000 | DL,DIM,ES | 0.9(w) 5.7(d) |
| 81327-SU | LFX/MP/8R/13W/MS/SCT | 13 | 1000 | 120 | 27K/30K/35K/40K/50K | 50000 | DL,DIM,ES | 0.9(w) 8.2(d) |
| 81329-SU | LFX/MP/12R/18W/MS/SCT | 18 | 1400 | 120 | 27K/30K/35K/40K/50K | 50000 | DL,DIM,ES | 0.9(w) 12.1(d) |